



## PRODUCT GUIDE

### Sandy Buff

Sandy Buff Sandstone is a natural stone excavated from the earth. Unlike concrete which is man-made, natural stone had been under intensive pressure and heat underground. Giving our paving slabs a unique look. Therefore to preserve this unique look and durability we recommend all customers read the following

Natural Stone characteristics are variation in colour, texture, blemishes, veining, holes and chippings to the corners and sides of the stone. Sample pieces provided by Barrow and Stone are small and will vary, they will not hold a true representation of the paving therefore we strongly suggest you talk to one of our trained staff about seeing larger pieces.

Do not spill any cement or mortar onto the Sandy Buff Sandstone, if so please clean off immediately with a wet cloth or sponge.

Before cleaning your Sandy Buff Sandstone please ask one of our trained friendly staff for professional guidance and that the conditions and environment are right for the desired area to have your Sandy Buff Sandstone

Sandy Buff Sandstone cannot be butt jointed we recommend that you use a 8-10mm gap.

Dimensional tolerance of Sandy Buff Sandstone +/- 4mm

Barrow and Stone will not refund or exchange the Sandy Buff Sandstone because of any variation in the stone or natural stone characteristics. Therefore we highly recommend that you order an extra 10% when ordering Sandy Buff Sandstone to account for wastage and any pieces that you may not like.

	WILLIAM SHAW	✉ <a href="mailto:william@barrowandstone.com">william@barrowandstone.com</a> ☎ +44 7453 643151	 
---	--------------	---	--